

**DOW CORNING(R) 732 MULTI-PURPOSE  
SEALANT WHITE**

Version 3.0      Revision Date: 09/14/2017      SDS Number: 1315260-00010      Date of last issue: 03/13/2017  
Date of first issue: 02/12/2015

---

**SECTION 1. IDENTIFICATION**

Product name : DOW CORNING(R) 732 MULTI-PURPOSE SEALANT  
WHITE

Product code : 000000000001890581

**Manufacturer or supplier's details**

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road  
Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900  
CHEMTREC : (800) 424-9300

**Recommended use of the chemical and restrictions on use**

Recommended use : Adhesive, binding agents

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Not a hazardous substance or mixture.

**GHS label elements**

Not a hazardous substance or mixture.

Precautionary Statements : **Prevention:**  
P271 Use only outdoors or in a well-ventilated area.

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Silicone elastomer

**Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
Silicon dioxide	7631-86-9	>= 8 - <= 9
Titanium dioxide	13463-67-7	>= 0.58 - <= 0.7

---

**SECTION 4. FIRST AID MEASURES**

DOW CORNING(R) 732 MULTI-PURPOSE  
SEALANT WHITE

Version	Revision Date:	SDS Number:	Date of last issue: 03/13/2017
3.0	09/14/2017	1315260-00010	Date of first issue: 02/12/2015

- |   |   |   |
|---|---|---|
| If inhaled  | : | If inhaled, remove to fresh air.<br>Get medical attention if symptoms occur.  |
| In case of skin contact                                     | : | Wash with water and soap as a precaution.<br>Get medical attention if symptoms occur.                                   |
| In case of eye contact                                      | : | Flush eyes with water as a precaution.<br>Get medical attention if irritation develops and persists.                    |
| If swallowed  | : | If swallowed, DO NOT induce vomiting.<br>Get medical attention if symptoms occur.<br>Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : | None known.   |
| Protection of first-aiders                                  | : | No special precautions are necessary for first aid responders.  |
| Notes to physician  | : | Treat symptomatically and supportively.   |

**SECTION 5. FIRE-FIGHTING MEASURES**

- |  |   |   |
|--|---|---|
| Suitable extinguishing media                   | : | Water spray<br>Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical  |
| Unsuitable extinguishing media                 | : | None known.   |
| Specific hazards during fire fighting          | : | Exposure to combustion products may be a hazard to health.  |
| Hazardous combustion products                  | : | Carbon oxides<br>Silicon oxides<br>Formaldehyde   |
| Specific extinguishing methods                 | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.<br>Use water spray to cool unopened containers.<br>Remove undamaged containers from fire area if it is safe to do so.<br>Evacuate area. |
| Special protective equipment for fire-fighters | : | Wear self-contained breathing apparatus for firefighting if necessary.<br>Use personal protective equipment.  |

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- |                               |   |   |
|-------------------------------|---|---|
| Personal precautions, protec- | : | Follow safe handling advice and personal protective |
|-------------------------------|---|---|

DOW CORNING(R) 732 MULTI-PURPOSE  
SEALANT WHITE

Version	Revision Date:	SDS Number:	Date of last issue: 03/13/2017
3.0	09/14/2017	1315260-00010	Date of first issue: 02/12/2015

tive equipment and emergency procedures

equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

## SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment. Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers. Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types: Strong oxidizing agents

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3

DOW CORNING(R) 732 MULTI-PURPOSE  
SEALANT WHITE

Version 3.0      Revision Date: 09/14/2017      SDS Number: 1315260-00010      Date of last issue: 03/13/2017  
Date of first issue: 02/12/2015

			(Silica)	
		TWA (Dust)	80 mg/m <sup>3</sup> / %SiO <sub>2</sub> (Silica)	OSHA Z-3
		TWA	6 mg/m <sup>3</sup> (Silica)	NIOSH REL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA	10 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH

**These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.**

|| Silicon dioxide

|| Titanium dioxide

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.  
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : paste

Color : white

Odor : Acetic acid

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 732 MULTI-PURPOSE SEALANT WHITE

Version 3.0      Revision Date: 09/14/2017      SDS Number: 1315260-00010      Date of last issue: 03/13/2017  
Date of first issue: 02/12/2015

---

Odor Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Self-ignition : The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : No data available

Relative density : 1.04

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

DOW CORNING(R) 732 MULTI-PURPOSE  
SEALANT WHITE

Version	Revision Date:	SDS Number:	Date of last issue: 03/13/2017
3.0	09/14/2017	1315260-00010	Date of first issue: 02/12/2015

- Reactivity : Not classified as a reactivity hazard.
- Chemical stability : Stable under normal conditions.
- Possibility of hazardous reactions : Use at elevated temperatures may form highly hazardous compounds.  
Can react with strong oxidizing agents.  
Acetic acid is formed upon contact with water or humid air.  
Hazardous decomposition products will be formed at elevated temperatures.
- Conditions to avoid : None known.
- Incompatible materials : Oxidizing agents

**Hazardous decomposition products**

Thermal decomposition : Formaldehyde

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Product:**

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: On basis of test data.
- Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: On basis of test data.

**Ingredients:****Silicon dioxide:**

- Acute oral toxicity : LD50 (Rat): > 3,300 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Information taken from reference works and the literature.
- Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

DOW CORNING(R) 732 MULTI-PURPOSE  
SEALANT WHITE

Version 3.0      Revision Date: 09/14/2017      SDS Number: 1315260-00010      Date of last issue: 03/13/2017  
Date of first issue: 02/12/2015

Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Information taken from reference works and the literature.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Information taken from reference works and the literature.

**Titanium dioxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**

Species: Rabbit  
Result: No skin irritation  
Remarks: On basis of test data.

**Ingredients:****Silicon dioxide:**

Result: No skin irritation  
Remarks: Information taken from reference works and the literature.

**Titanium dioxide:**

Species: Rabbit  
Result: No skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Species: Rabbit  
Result: No eye irritation  
Remarks: On basis of test data.

**Ingredients:****Silicon dioxide:**

Result: No eye irritation

DOW CORNING(R) 732 MULTI-PURPOSE  
SEALANT WHITE

Version 3.0      Revision Date: 09/14/2017      SDS Number: 1315260-00010      Date of last issue: 03/13/2017  
Date of first issue: 02/12/2015

Remarks: Information taken from reference works and the literature.

**Titanium dioxide:**

Species: Rabbit  
Result: No eye irritation

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Ingredients:****Silicon dioxide:**

Assessment: Does not cause skin sensitization.

Test Type: Skin: test type not specified  
Species: Guinea pig  
Result: negative  
Remarks: Information taken from reference works and the literature.

**Titanium dioxide:**

Test Type: Local lymph node assay (LLNA)  
Routes of exposure: Skin contact  
Species: Mouse  
Result: negative

**Germ cell mutagenicity**

Not classified based on available information.

**Ingredients:****Silicon dioxide:**

Genotoxicity in vitro : Result: negative  
Remarks: Information taken from reference works and the literature.

Genotoxicity in vivo : Application Route: Ingestion  
Result: negative  
Remarks: Information taken from reference works and the literature.

Germ cell mutagenicity - Assessment : Animal testing did not show any mutagenic effects.

**Titanium dioxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative



DOW CORNING(R) 732 MULTI-PURPOSE  
SEALANT WHITE

Version	Revision Date:	SDS Number:	Date of last issue: 03/13/2017
3.0	09/14/2017	1315260-00010	Date of first issue: 02/12/2015

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Ingredients:****Titanium dioxide:**

Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Exposure time: 24 Months  
Method: OECD Test Guideline 453  
Result: positive  
Remarks: The mechanism or mode of action may not be relevant in humans.  
These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

**IARC**

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Not classified based on available information.

**Repeated dose toxicity****Ingredients:****Titanium dioxide:**

Species: Rat  
NOAEL: 24,000 mg/kg  
Application Route: Ingestion  
Exposure time: 28 Days

Species: Rat

DOW CORNING(R) 732 MULTI-PURPOSE  
SEALANT WHITE

Version	Revision Date:	SDS Number:	Date of last issue: 03/13/2017
3.0	09/14/2017	1315260-00010	Date of first issue: 02/12/2015

NOAEL: 10 mg/m<sup>3</sup>  
 Application Route: inhalation (dust/mist/fume)  
 Exposure time: 2 y  
 Remarks: These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

**Aspiration toxicity**

Not classified based on available information.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:****Titanium dioxide:**

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae	:	EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l Exposure time: 72 h
Toxicity to microorganisms	:	EC50: > 1,000 mg/l Exposure time: 3 h Method: OECD Test Guideline 209

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Resource Conservation and Recovery Act (RCRA)	:	This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.
Waste from residues	:	Dispose of in accordance with local regulations.
Contaminated packaging	:	Empty containers should be taken to an approved waste

DOW CORNING(R) 732 MULTI-PURPOSE  
SEALANT WHITE

Version	Revision Date:	SDS Number:	Date of last issue: 03/13/2017
3.0	09/14/2017	1315260-00010	Date of first issue: 02/12/2015

handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

## SECTION 14. TRANSPORT INFORMATION

## International Regulations

## UNRTDG

Not regulated as a dangerous good

## IATA-DGR

Not regulated as a dangerous good

## IMDG-Code

Not regulated as a dangerous good

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## Domestic regulation

## 49 CFR

Not regulated as a dangerous good

## SECTION 15. REGULATORY INFORMATION

## EPCRA - Emergency Planning and Community Right-to-Know

## CERCLA Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Acetic acid	64-19-7	5000	*
Acetic anhydride	108-24-7	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

## SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## US State Regulations

## Pennsylvania Right To Know

Dimethyl siloxane, hydroxy-terminated	70131-67-8
Silicon dioxide	7631-86-9
Acetic acid	64-19-7
Acetic anhydride	108-24-7

# DOW CORNING(R) 732 MULTI-PURPOSE SEALANT WHITE

Version	Revision Date:	SDS Number:	Date of last issue: 03/13/2017
3.0	09/14/2017	1315260-00010	Date of first issue: 02/12/2015

### California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

### California Permissible Exposure Limits for Chemical Contaminants

Silicon dioxide	7631-86-9
-----------------	-----------

### The ingredients of this product are reported in the following inventories:


- |           |  |
|-----------|--|
| NZIoC     | : All ingredients listed or exempt.  |
| TSCA      | : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.  |
| PICCS     | : All ingredients listed or exempt.  |
| KECI      | : All ingredients listed, exempt or notified.  |
| ENCS/ISHL | : All components are listed on ENCS/ISHL or exempted from inventory listing.   |
| IECSC     | : All ingredients listed or exempt.  |
| AICS      | : All ingredients listed or exempt.  |
| DSL       | : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).   |
| REACH     | : For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office. |
| TCSI      | : All ingredients listed or exempt.  |

DOW CORNING(R) 732 MULTI-PURPOSE  
SEALANT WHITEVersion  
3.0Revision Date:  
09/14/2017SDS Number:  
1315260-00010Date of last issue: 03/13/2017  
Date of first issue: 02/12/2015

## SECTION 16. OTHER INFORMATION

## Further information

## NFPA:



## HMIS® IV:

HEALTH	/	0
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

## Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Oth-

**DOW CORNING(R) 732 MULTI-PURPOSE  
SEALANT WHITE**

Version	Revision Date:	SDS Number:	Date of last issue: 03/13/2017
3.0	09/14/2017	1315260-00010	Date of first issue: 02/12/2015

---

erwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/14/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8