E TRANSLICER® BIAS CUTTER

BATCH PROCESSING FOR NICHE MARKETS

Newly developed parts transform the "E TranSlicer" Cutter (METRS) from standard slicing to either **35 or 45 degree** bias flat or crinkle slicing. Available when ordering a new machine, or as a retrofit kit for E TranSlicer machines in the field.

Once retrofitted, switching over from straight to bias slicing is accomplished in as little as 10 minutes.

Designed for hand-fed, batch processing (running at 30 Hz) equipped with a [®]MicroSlice[®] or slicing wheel set-up.

Product is fed through a top chute that delivers product to the slicing wheel to produce bias slices. Infeed product should not exceed 2.5" (63.5 mm) in diameter.



BIAS CUTS



A. SLICING WHEEL Flat & Crinkle Slices: 1/32 to 3" (.8 to 76.2 mm) Crinkle slices have 4-2/3 waves per inch and with a crinkle depth of 1/16" (1.6 mm).



B. MICROSLICE® WHEEL

Flat Slices: .020 to .240"

(.5 to 6 mm)

Crinkle Slice: .069" (1.8 mm) thickness with 3-1/3 waves per inch and a crinkle depth of .080" (2.0 mm)









LEEK 3/16" (4.8 mm)

GREEN BEAN 1/4" (6.4 mm)

3/16" (4.8 mm) Crinkle

PICKLE 3/16" (4.8 mm)

JALAPEÑO 3/16" (4.8 mm)










PARTS OVERVIEW



- 1. Bias Sliding Hood
- 2. Infeed Bias Chute
- 3. Bias Chute Assembly
- 4. Bias Chute Mounting Bracket
- **5.** Slicing Wheel


E TRANSLICER® BIAS CUTTER

Measurements and weights may vary depending on machine configuration.

 Length:
 100.78" (2560 mm)
 Net Weight:
 1300 lb (560 kg)

 Width:
 35.31" (897 mm)
 Cutting Wheel Motor:
 3 HP (2.2 kW)

 Height:
 72.30" (1836 mm)
 Feed Belt Motor:
 1 HP (.75 kW)



TEST CUT YOUR PRODUCT

Contact your local Urschel representative to schedule a comprehensive, no-obligation test-cut of your product: **www.urschel.com.**

