

**Revision Number: 004.0** Issue date: 08/28/2017

## PRODUCT AND COMPANY IDENTIFICATION

**Product name:** LOCTITE LB 8423 DIELECTRIC

GREASE known as Dielectric Grease

Product type: Lubricant Restriction of Use: None identified

Company address:

One Henkel Way

Rocky Hill, Connecticut 06067

Henkel Corporation

IDH number: 270640

30536 Item number: Region: United States

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

### 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW	
NOT CLASSIFIED. READ ENTIRE SAFETY DATA SHEET.	

HAZARD CLASS	HAZARD CATEGORY
None	None

PICTOGRAM(S)
None

#### **Precautionary Statements**

Prevention: Not prescribed Response: Not prescribed Not prescribed Storage: Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Silica, amorphous, fumed, crystal-free	112945-52-5	5 - 10

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms develop and persist, get medical attention. If

breathing is difficult, give oxygen. Get immediate medical attention.

Skin contact: Wash with soap and water. If symptoms develop and persist, get medical

attention.

Product name: LOCTITE LB 8423 DIELECTRIC GREASE known as Dielectric Grease IDH number: 270640 Page 1 of 5

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. If eye irritation persists, consult a specialist.

**Ingestion:** Do not induce vomiting. Get medical attention.

Symptoms: See Section 11.

## 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special fire fighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat.

**Hazardous combustion products:** Oxides of carbon. Formaldehyde. Toxic and irritating vapors.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, is olate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Ventilate area. Do not allow product to enter sew er or waterways.

Clean-up methods: Scrape up spilled material and place in a closed container for disposal.

### 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation.

Storage: Keep aw ay from heat, spark and flame. Keep in a cool, well ventilated area.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None

Engineering controls: Use local ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s). Observe OSHA regulations for respirator use (29 CFR 1910.134).

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:** Chemical resistant, impermeable gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid
Color: Clear
Odor: Mild

IDH number: 270640

Odor threshold:

PH:

Not available.

Not applicable

Vapor pressure: <5 mm hg (77 °F (25°C))

Product name: LOCTITE LB 8423 DIELECTRIC GREASE known as Dielectric Grease

Page 2 of 5

Boiling point/range: > 300 °F (> 148.9 °C)None

Melting point/ range: Not available.

Specific gravity: 0.86

Vapor density: Heavier than air.

Flash point: > 260 °C (> 500°F) HST-US D09F; Flash/Fire Point By Cleveland Open Cup

Flam m able/Explosive limits - lower:
Flam m able/Explosive limits - upper:
Autoignition temperature:
Flam m ability:
Fvaporation rate:
Solubility in water:
Not available.
Not available.

Partition coefficient (n-octanol/water): More soluble in octanol.

VOC content: 0 %; 0 g/l Viscosity: Not available. Decomposition temperature: Not available.

### 10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 270640

Formaldehyde. Oxides of carbon.

**Incompatible materials:** Strong acids and strong bases. Strong oxidizing agents.

Reactivity: Not available.

**Conditions to avoid:** Excessive heat. Store away from incompatible materials.

### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation: When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may

formformaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit. Mist or spray may cause respiratory tract irritation and delayed onset pulmonary edema.

Skin contact: May cause skin irritation.

Eye contact: May cause eye irritation.

Ingestion: Not expected under normal conditions of use. May cause gastrointestinal tract irritation if

sw allowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Silica, amorphous, fumed, crystal-free	None	Nuisance dust

Haranda va Camp an ant/a)	ATTR Consideration		OSHA Carcinogen
Hazardous Component(s)	zardous Component(s) NTP Carcinogen	IARC Carcinogen	(Specifically Regulated)
Silica, amorphous, fumed, crystal-free	No	No	No

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

Product name: LOCTITE LB 8423 DIELECTRIC GREASE known as Dielectric Grease

Page 3 of 5

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

## 15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis. CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

IDH number: 270640

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2, 3, 11

Prepared by: Product Safety and Regulatory Affairs

Issue date: 08/28/2017

Product name: LOCTITE LB 8423 DIELECTRIC GREASE known as Dielectric Grease

Page 4 of 5

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. How ever, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all w arranties, express or implied, including w arranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Product name: LOCTITE LB 8423 DIELECTRIC GREASE known as Dielectric Grease Page 5 of 5

IDH number: 270640